

# Coda Audio D-Series

## D5-Cube

**CODA**  
C O D A A U D I O



The D5-Cube is an ultra compact 2-way coaxial point source speaker system, containing one high power 5" woofer and a coaxially mounted 44.4mm voice coil driver. The design aligns the acoustical centres of the transducers to produce a single point source, providing a coherent wave front without hot spots. With precise directivity of 90° conical, uniform coverage is ensured. The attractive solid wood design and superb sound quality allows the D5-Cube to be used in a wide range of critically sensitive applications, such as, conferences, Houses of Worship, airport and other transport hubs, convention centres, restaurant and bars.

### Key features:

- Coda Audio high output time aligned transducers
- 16 Ohm design for ease of multiple chaining
- Solid aluminium construction
- U-bracket, mic stand, or wall mount accessories
- Ultra compact size
- Maximum SPL peak: 117 dB
- Weatherproof option
- All RAL-colours optional
- 100 V Trans, 100 VA option

### Key advantages:

- Outstanding audio quality
- Exemplary component reliability
- Flexible accessory package
- Expandable user application area with introduction of subwoofer system
- Competitive price point advantage

### Applications:

- State-of-the-art solution for all high quality near field applications
- On stage near field monitoring
- Conferences, Houses of Worship, transport hubs, convention centres
- Restaurants, bars, 5.1 surround sound



### Need more?

The addition of the appropriate Coda Audio subwoofer expands frequency response and application area greatly. The D8 2-way full range system will supply increased frequency response and output power.

### Need less?

Few professional applications would require less than a D5-Cube. Take a look at the D5-Tube and D5-Ceiling for alternative placement options.

### Technical specifications:

Type:	2-way coaxial ultra compact
Application:	Superior quality short throw
Frequency response:	90 Hz – 30 kHz (-3 dB)
Power handling AES:	125 W
Program power:	250 W
Peak power:	500 W
Sensitivity:	91 dB
Max. SPL peak:	117 dB
Dispersion:	90° conical
<b>Components:</b>	
Low frequency:	5" woofer, 1.5" (38 mm) voice coil, 120 W (AES)
High frequency:	1" coaxially mounted driver, 1.75" (44.4 mm) voice coil, 80 W (AES)
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ω
100V version (optional):	100 VA
Input connectors:	Push buttons
Suspension:	6 x M6 threaded points
Enclosure material:	12 / 15 mm birch plywood
Finish:	Black paint (all RAL-colours optional)
Weatherproof version:	Optional
Flying hardware:	M6 treaded points
Dimensions (WxHxD):	160 x 160 x 160 mm
Net weight:	3.5 kg

Coda Audio D5-Cube fact sheet (1 of 2)

# Coda Audio D-Series


## D5-Cube

# CODA

C O D A A U D I O




### Accessories:




**CU5DC**  
Vertical U-bracket

- Certified vertical U-bracket for D5-Cube
- Easy to install and use
- Allows for vertical cabinet placement from a fixed point or suspension from trussing
- Included with D5-Cube




100 V Transformer, 100 VA



**24185**  
Wall mount

- Certified fixed wall mount bracket



Stand fitting 195/8

### System components:

AC24VS-UC	Analogue Controller
PW112	Subwoofer
PW12A	Active subwoofer
C-Series	Amplifiers

### EASE data:

EASE data is available from the Support Downloads area at [www.codaaudio.com](http://www.codaaudio.com).

### CAD/Drawing data:

Further product information including 2D and 3D CAD drawings are available from the Support Downloads area at [www.codaaudio.com](http://www.codaaudio.com).

