

D5-Cube



D5-Cube

2- way passive installation system

- Ultra compact 2-way coaxial system
- Coda Audio 5"/1" coaxial loudspeaker
- Attractive solid aluminium design
- Single point source system providing coherent wave front
- Superb quality sound
- Impedance 16 Ohm for easy daisy chaining
- System components: DNC260, C-Series Amplifiers, PW112, PW12A

The Coda D5-Cube is a passive 2-way 5" / 1" coaxial loudspeaker system designed without compromise to provide a true one point source in an ultra compact package. The cabinet contains a high power 5" woofer and a coaxially mounted driver with 44.4 mm voice coil. The advanced design aligns the acoustical centres of the transducers to produce a single point source. This unique loudspeaker technology provides a coherent wave front without hot spots. Precise directivity of 90° conical ensures uniform coverage with perfect time alignment between the components. Supported with a full range of mounting and flying accessories the D5-Cube sets a state-of-the-art solution for almost any high quality, near field installed sound reinforcement applications.

Supported with a full range of mounting and flying accessories the D5-Tube sets a state of the art solution for almost any high quality, near field installed sound reinforcement applications, such as conferences, restaurants, pubs,

shopping centres, clubs, convention centres, houses of worship, airports and 5.1 surround.

Also available D5-Cube 100 V including 100 V trafo, 100 VA.

TECHNICAL SPECIFICATIONS D5-Cube

Type	2-way coaxial ultra compact
Application:	Superior quality short throw
Frequency response:	90 Hz - 30 kHz (-3 dB)
Power handling AES:	125 W
Program power:	250 W
Peak Power:	500 W
Sensitivity:	91 dB
Max. SPL peak:	117 dB
Dispersion:	90° conical
Components:	
Low frequency:	5" woofer, 1.5" (38 mm) voice coil, 120 W (AES)
High frequency:	1" coaxially mounted driver, 1.75" (44.4 mm) voice coil, 80 W (AES)
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ω
100 V version (optional):	100 VA
Input connectors:	Push buttons
Enclosure material:	12/15 mm birch multiplex
Weatherproof version:	Optional
Suspension:	M6 threaded points, 3/8 thread for stand
Dimensions (WxHxD):	160x160x160 mm
Net weight:	3.5 kg

ACCESSORIES

CU5DC	Vertical U-bracket for D5-Cube (included in delivery)
24185	Wall Mount for D5-Cube
24471	Wall Mount for D5-Cube
A68620	Truss Clamp for D5-Cube